

Safety Data Sheet

Material Name: MIXED 2-BUTENE

SDS ID: 00233392

*** Section 1 - PRODUCT AND COMPANY IDENTIFICATION ***

Material Name: MIXED 2-BUTENE

Manufacturer Information

ADVANCED GAS TECHNOLOGIES

Phone: 1-800-416-2505

1401 Stauffer Road

Palm, PA 18070-0035

Emergency # 1-800-424-9300 (CHEMTREC)

Mfg Contact: Outside the US: 703-572-3887 (Collect Calls Accepted)

Chemical Family

hydrocarbons, aliphatic

Synonyms

*** Section 2 - HAZARDS IDENTIFICATION ***

EMERGENCY OVERVIEW

Color: colorless

Physical Form: gas

Odor: distinct odor, olefin odor

Health Hazards: difficulty breathing

POTENTIAL HEALTH EFFECTS

Inhalation

Short Term: irritation, nausea, vomiting, irregular heartbeat, headache, drowsiness, symptoms of drunkenness, suffocation, lung congestion

Long Term: liver damage

Skin

Short Term: frostbite

Long Term: no information on significant adverse effects

Eye

Short Term: frostbite, blurred vision

Long Term: no information on significant adverse effects

Ingestion

Short Term: frostbite

Long Term: no information is available

*** Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS ***

*** Section 4 - FIRST AID MEASURES ***

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Safety Data Sheet

Material Name: MIXED 2-BUTENE

SDS ID: 00233392

Eyes

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If a large amount is swallowed, get medical attention.

Note to Physicians

For inhalation, consider oxygen.

* * * Section 5 - FIRE FIGHTING MEASURES * * *

See Section 9 for Flammability Properties

NFPA Ratings: Health: Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Flammable Properties

Severe fire hazard. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Gas/air mixtures are explosive.

Extinguishing Media

carbon dioxide regular dry chemical

Large fires: Flood with fine water spray.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking. Stop flow of gas. Be aware that a BLEVE (Boiling Liquid Expanding Vapor Explosion) may occur unless surfaces are kept cool with water.

* * * Section 6 - ACCIDENTAL RELEASE MEASURES * * *

Occupational spill/release

Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

* * * Section 7 - HANDLING AND STORAGE * * *

Storage Procedures

Store in a well-ventilated area. Grounding and bonding required. Use explosion-resistant electrical equipment. Use non-sparking tools and equipment. Protect from physical damage. Store in a cool, dry place. Store below 54 C.

Safety Data Sheet

Material Name: MIXED 2-BUTENE

SDS ID: 00233392

*** Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ***

Component Analysis

ACGIH, OSHA and NIOSH have not developed exposure limits for any of this product's components.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Glove Recommendations

Wear insulated gloves.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

*** Section 9 - PHYSICAL AND CHEMICAL PROPERTIES ***

Physical State: Gas	Appearance: Not available
Color: colorless	Physical Form: gas
Odor: distinct odor, olefin odor	Odor Threshold: Not available
Melting Point: Not available	Boiling Point: 1.7 °C
Flash Point: -70.5 °C (estimated)	LEL: 1.8 %
UEL: 9.7 %	Vapor Pressure: 27.3 psia @ 21 °C
Vapor Density (air = 1): Not available	Water Solubility: insoluble

*** Section 10 - STABILITY AND REACTIVITY ***

Chemical Stability

Stable at normal temperatures and pressure.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

Materials to Avoid

halogens, oxidizing materials.

Decomposition Products

oxides of carbon

Safety Data Sheet

Material Name: MIXED 2-BUTENE

SDS ID: 00233392

Possibility of Hazardous Reactions

Will not polymerize.

*** Section 11 - TOXICOLOGICAL INFORMATION ***

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, OSHA or DFG.

*** Section 12 - ECOLOGICAL INFORMATION ***

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

*** Section 13 - DISPOSAL CONSIDERATIONS ***

Disposal Methods

Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. Dispose in accordance with all applicable regulations.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

*** Section 14 - TRANSPORT INFORMATION ***

US DOT Information

Shipping Name: Butylene
UN/NA #: UN1012 **Hazard Class:** 2.1
Required Label(s): 2.1

TDG Information

Shipping Name: Butylene
UN #: UN1012 **Hazard Class:** 2.1
Required Label(s): 2.1

*** Section 15 - REGULATORY INFORMATION ***

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA 311/312

Acute Health: Yes **Chronic Health:** No **Fire:** Yes **Pressure:** Yes **Reactive:** No

U.S. State Regulations

None of this product's components are listed on the state lists from CA, MA, MN, NJ, PA, or RI.

Not regulated under California Proposition 65

Component Analysis - Inventory

No information is available.

Safety Data Sheet

Material Name: MIXED 2-BUTENE

SDS ID: 00233392

*** Section 16 - OTHER INFORMATION ***

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

End of Sheet 00233392