

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

*** Section 1 - PRODUCT AND COMPANY IDENTIFICATION ***

Material Name: PROPANE

Manufacturer Information

ADVANCED GAS TECHNOLOGIES

Phone: 1-800-416-2505

1401 Stauffer Road

Palm, PA 18070-0035

Emergency # 1-800-424-9300 (CHEMTREC)

Mfg Contact: Outside the US: 703-572-3887 (Collect Calls Accepted)

Chemical Family

hydrocarbons, aliphatic

Synonyms

Mtg msds 76; n-Propane; Dimethylmethane; Propyl hydride; R-290; Propylhydride; Liquefied petroleum gas; Lpg; >96% natural grade; >99.9% pure grade; UN 1978; C3H8; RTECS: TX2275000

*** Section 2 - HAZARDS IDENTIFICATION ***

EMERGENCY OVERVIEW

Color: colorless

Physical Form: gas

Odor: gasoline odor

Health Hazards: central nervous system depression, difficulty breathing

Physical Hazards: Flammable gas. May cause flash fire.

POTENTIAL HEALTH EFFECTS

Inhalation

Short Term: nausea, vomiting, irregular heartbeat, headache, symptoms of drunkenness, disorientation, suffocation, convulsions, coma

Long Term: same as effects reported in short term exposure

Skin

Short Term: blisters, frostbite

Long Term: no information on significant adverse effects

Eye

Short Term: frostbite, blurred vision

Long Term: no information is available

Ingestion

Short Term: frostbite

Long Term: no information is available

*** Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS ***

CAS	Component	Percent
74-98-6	Propane	>96

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Aliphatic hydrocarbon gases (Alkane [C1-C4]).

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

*** Section 4 - FIRST AID MEASURES ***

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Eyes

Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If a large amount is swallowed, get medical attention.

Note to Physicians

For inhalation, consider oxygen.

*** Section 5 - FIRE FIGHTING MEASURES ***

See Section 9 for Flammability Properties

NFPA Ratings: Health: 1 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Flammable Properties

Severe fire hazard. Severe explosion hazard. Gas/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Extinguishing Media

carbon dioxide regular dry chemical
Large fires: Flood with fine water spray.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Stop flow of gas.

*** Section 6 - ACCIDENTAL RELEASE MEASURES ***

Occupational spill/release

Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

*** Section 7 - HANDLING AND STORAGE ***

Storage Procedures

Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.110. Grounding and bonding required. U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

*** Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ***

Component Analysis

Propane (74-98-6)

ACGIH:	1000 ppm TWA
OSHA (final):	1000 ppm TWA; 1800 mg/m3 TWA
OSHA (vacated):	1000 ppm TWA; 1800 mg/m3 TWA
NIOSH:	1000 ppm TWA; 1800 mg/m3 TWA

IDLH

2100 ppm

Ventilation

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Glove Recommendations

Wear insulated gloves.

Respiratory Protection

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA.
2100 ppm

Any supplied-air respirator.

Any self-contained breathing apparatus with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions -

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Escape -

Any appropriate escape-type, self-contained breathing apparatus.

*** Section 9 - PHYSICAL AND CHEMICAL PROPERTIES ***

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

Physical State: Gas	Appearance: Not available
Color: colorless	Physical Form: gas
Odor: gasoline odor	Odor Threshold: 5000 - 20000 ppm
Melting Point: -190 °C	Boiling Point: -40 °C
Flash Point: -105 °C	LEL: 2.1 %
UEL: 9.5 %	Vapor Pressure: 6398 mmHg @ 21.1 °C
Vapor Density (air = 1): 1.55	Specific Gravity (water = 1): 0.5853 @ -45 °C
Water Solubility: very slightly soluble	Auto Ignition: 450 °C
Molecular Weight: 44.11	Molecular Formula: C-H3-C-H2-C-H3

Solvent Solubility

Soluble: absolute alcohol, ether, chloroform, benzene, turpentine

* * * Section 10 - STABILITY AND REACTIVITY * * *

Chemical Stability

Stable at normal temperatures and pressure.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

Materials to Avoid

oxidizing materials, combustible materials.

Decomposition Products

oxides of carbon

Possibility of Hazardous Reactions

Will not polymerize.

* * * Section 11 - TOXICOLOGICAL INFORMATION * * *

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Propane (74-98-6)

Inhalation LC50 Rat: 658 mg/L/4H

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, OSHA or DFG.

Target Organs

Propane (74-98-6)

central nervous system.

Additional Data

Stimulants such as epinephrine may induce ventricular fibrillation.

* * * Section 12 - ECOLOGICAL INFORMATION * * *

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

*** Section 13 - DISPOSAL CONSIDERATIONS ***

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.

Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

*** Section 14 - TRANSPORT INFORMATION ***

US DOT Information

Shipping Name: Propane

UN/NA #: UN1978 Hazard Class: 2.1

Required Label(s): 2.1

TDG Information

Shipping Name: Propane

UN #: UN1978 Hazard Class: 2.1

Required Label(s): 2.1

*** Section 15 - REGULATORY INFORMATION ***

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA 311/312

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: Yes Reactive: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Propane	74-98-6	No	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Propane	74-98-6	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

Safety Data Sheet

Material Name: PROPANE

SDS ID: 00233341

*** Section 16 - OTHER INFORMATION ***

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

End of Sheet 00233341