

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

*** Section 1 - PRODUCT AND COMPANY IDENTIFICATION ***

Material Name: PROPYLENE

Manufacturer Information

ADVANCED GAS TECHNOLOGIES

Phone: 1-800-416-2505

1401 Stauffer Road

Palm, PA 18070-0035

Emergency # 1-800-424-9300 (CHEMTREC)

Mfg Contact: Outside the US: 703-572-3887 (Collect Calls Accepted)

Chemical Family

hydrocarbons, aliphatic

Synonyms

Mtg msds 77; Propene; Methylethene; Methylethylene; 1-Propylene; 1-Propene; UN 1077; C3H6; RTECS: UC6740000

*** Section 2 - HAZARDS IDENTIFICATION ***

EMERGENCY OVERVIEW

Color: colorless

Physical Form: gas

Health Hazards: central nervous system depression, difficulty breathing

Physical Hazards: Flammable gas. May cause flash fire.

POTENTIAL HEALTH EFFECTS

Inhalation

Short Term: tearing, nausea, vomiting, symptoms of drunkenness, suffocation, convulsions, coma

Long Term: no information on significant adverse effects

Skin

Short Term: blisters, frostbite

Long Term: no information is available

Eye

Short Term: frostbite, blurred vision

Long Term: no information is available

Ingestion

Short Term: frostbite

Long Term: no information is available

*** Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS ***

CAS	Component	Percent
115-07-1	Propylene	100.0

*** Section 4 - FIRST AID MEASURES ***

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Eyes

Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If a large amount is swallowed, get medical attention.

Note to Physicians

For inhalation, consider oxygen.

*** Section 5 - FIRE FIGHTING MEASURES ***

See Section 9 for Flammability Properties

NFPA Ratings: Health: 1 Fire: 4 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Flammable Properties

Severe fire hazard. Vapor/air mixtures are explosive above flash point. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Extinguishing Media

carbon dioxide regular dry chemical

Large fires: Flood with fine water spray.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Stop flow of gas.

*** Section 6 - ACCIDENTAL RELEASE MEASURES ***

Occupational spill/release

Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

*** Section 7 - HANDLING AND STORAGE ***

Storage Procedures

Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.110. Protect from physical damage. Store in a cool, dry place. Store in a well-ventilated area. Avoid heat, flames, sparks and other sources of ignition. Store outside or in a detached building. Grounding and bonding required. U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

*** Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION ***

Component Analysis

Propylene (115-07-1)

ACGIH: 500 ppm TWA

Ventilation

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Glove Recommendations

Wear insulated gloves.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

*** Section 9 - PHYSICAL AND CHEMICAL PROPERTIES ***

Physical State: Gas	Appearance: Not available
Color: colorless	Physical Form: gas
Odor: Not Available	Odor Threshold: Not available
Melting Point: -185 °C	Boiling Point: -47 °C
Flash Point: -108 °C	LEL: 2.0 %
UEL: 11.1 %	Vapor Pressure: 7828 mmHg @ 21.1 °C
Henry's Law Constant: 0.00096317 atm-m ³ /mol	Vapor Density (air = 1): 1.5
Density: 1.7855 g/L	Water Solubility: 45 %
KOW: 223.87 (estimated from water solubility)	KOC: 533.33 (estimated from water solubility)
Auto Ignition: 455 °C	Viscosity: 0.140 cP @ -40 °C
Molecular Weight: 42.08	Molecular Formula: C-H ₃ -C-H-C-H ₂

Solvent Solubility

Soluble: alcohol, ether, acetic acid

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

*** Section 10 - STABILITY AND REACTIVITY ***

Chemical Stability

May polymerize. May react on contact with air, heat, light or water.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

Materials to Avoid

oxidizing materials, halo carbons, halogens, acids.

Decomposition Products

miscellaneous decomposition products

Possibility of Hazardous Reactions

May polymerize. Avoid contact with heat, light, air, water or incompatible materials. Polymerizes with evolution of heat.

*** Section 11 - TOXICOLOGICAL INFORMATION ***

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Propylene (115-07-1)

Inhalation LC50 Rat: 658 mg/L/4H

Component Carcinogenicity

Propylene (115-07-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 60 [1994]; Supplement 7 [1987] (Group 3 (not classifiable))

Target Organs

Propylene (115-07-1)

central nervous system.

Additional Data

Stimulants such as epinephrine may induce ventricular fibrillation.

*** Section 12 - ECOLOGICAL INFORMATION ***

Component Analysis - Aquatic Toxicity

No LOEL ecotoxicity data are available for this product's components.

*** Section 13 - DISPOSAL CONSIDERATIONS ***

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

*** Section 14 - TRANSPORT INFORMATION ***

US DOT Information

Shipping Name: Propylene

UN/NA #: UN1077 Hazard Class: 2.1

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

Required Label(s): 2.1

TDG Information

Shipping Name: Propylene

UN #: UN1077 Hazard Class: 2.1

Required Label(s): 2.1

*** Section 15 - REGULATORY INFORMATION ***

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Propylene (115-07-1)

SARA 313: 1.0 % de minimis concentration

SARA 311/312

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: Yes Reactive: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Propylene	115-07-1	Yes	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Propylene	115-07-1	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

*** Section 16 - OTHER INFORMATION ***

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

Safety Data Sheet

Material Name: PROPYLENE

SDS ID: 00233340

End of Sheet 00233340