ETHYLENE (C_2H_4)

A flammable, colorless gas, with a characteristic sweet odor.

Purity Specifications	Grade 2.5 99.5%	Grade 3.0 99.9%	Grade 3.5 99.95%	Grade 4.0 99.99%	Grade 4.5 99.995%
Nitrogen	< 100 ppm	< 100 ppm	< 50 ppm	< 5 ppm	< 5 ppm
Oxygen	< 25 ppm	< 20 ppm	< 10 ppm	< 2 ppm	< 2 ppm
Carbon Dioxide	< 15 ppm	< 10 ppm	< 10 ppm	< 5 ppm	< 5 ppm
Carbon Monoxide	< 5 ppm	< 3 ppm	< 3 ppm	< 2 ppm	< 2 ppm
Other Hydrocarbons	< 4000 ppm	< 800 ppm	< 400 ppm	< 80 ppm	< 40 ppm
Acetylene	< 10 ppm	< 8 ppm	< 6 ppm	< 4 ppm	< 4 ppm
Moisture	< 5 ppm	< 5 ppm	< 5 ppm	< 5 ppm	< 5 ppm
Total Impurities	< 5000 ppm	< 1000 ppm	< 500 ppm	< 100 ppm	< 50 ppm

Purity Specifications	Grade 5.0 99.999%	Grade 5.5 99.9995%
Nitrogen	< 2 ppm	< 1 ppm
Oxygen	< 2 ppm	< 1 ppm
Carbon Dioxide	< 2 ppm	< 1 ppm
Carbon Monoxide	< 2 ppm	< 1 ppm
Other Hydrocarbons	< 8 ppm	< 4 ppm
Acetylene	< 2 ppm	< 1 ppm
Moisture	< 3 ppm	< 1 ppm
Total Impurities	< 10 ppm	< 5 ppm

Moisture level guaranteed only when AGT prepares the cylinders.
All concentrations are on a mol/mol basis unless otherwise stated.
This product is analyzed gas phase.

Cylinder Size	Fill Weight (lbs)
49	37.0
44	30.0
16	11.0
7	4.0

Technical Data:

Mol. Wt: 28.054
Sp. Volume: . . . . . 13.8 cu. ft/lb
Flammability Limits: . . . . . 2.7 - 36% in Air
Valve Outlet: . . . . . CGA 350
LB CGA 170

Shipping Information:

DOT Name: . . . . . Ethylene, Compressed
Hazard Class: 2.1
DOT No.: . . . . . UN 1962
DOT Label: . . . . . Flammable Gas
CAS No.: 74-85-1

ADVANCED GAS TECHNOLOGIES
1401 Stauffer Road, Palm, PA 18070 • Phone: 215-541-4116 / 215-541-4117 • Fax: 215-541-4443 • Email: info@advgas.com